



2SGP(m)

- Application Limits
- ◉ Suction head up to 8m
  - ◉ Liquid temperature up to +40°C
  - ◉ Ambient temperature up to +40°C
  - ◉ Max. Working pressure: 5bar
  - ◉ Voltage fluctuation should not exceed 10% of rated value.
  - ◉ pH: 6.5 to 8.5
- Advantages & Features
- ◉ Double impeller centrifugal pump, satisfies the requirement of high head.
  - ◉ Compact structure

Model		Power		Max. Flow	Max. Head	Head Range	Max. Suction	Packing Dim.	G.W.	20'Loading Qty.
Single-Phase	Three-Phase	kW	HP	(m³/h)	(m)	(m)	(m)	(L×W×H) mm	(kg)	(pcs)
2SGPm25/130	2SGP25/130	0.75	1	6	42	7~42	8	385×235×280	18/17.5	1270
2SGPm25/140	2SGP25/140	1.1	1.5	10.2	42	17~42	8	445×255×300	24/24	885
2SGPm25/160	2SGP25/160B	1.5	2	12	50	22~50	8	445×255×300	27/26.5	885



PUM

- Application Limits
- ◉ Suction head up to 8m
  - ◉ Liquid temperature up to +90°C
  - ◉ Ambient temperature up to +40°C
  - ◉ Max. Working pressure: 3bar
  - ◉ Voltage fluctuation should not exceed 10% of rated value.
  - ◉ pH: 6.5 to 8.5
- Advantages & Features
- ◉ Stainless steel impeller, shaft 304
  - ◉ Specially designed for view of the hot water circulation
  - ◉ High quality mechanical seal, NSK bearing, improve the reliability of the product

Model		Power		Max. Flow	Max. Head	Head Range	Max. Suction	Packing Dim.	G.W.	20'Loading Qty.
Single-Phase		kW	HP	(m³/h)	(m)	(m)	(m)	(L×W×H) m	(kg)	(pcs)
PUM200		0.25	0.34	5	15.5	7~15.5	8	310×205×240	8	1881
PUM400		0.55	0.75	6.3	22	8~22	8	380×235×285	12	1232
PUM600		0.75	1	7.2	27	16~27	8	380×235×285	13.5	1232